



MODEL BF



SPECIFICATIONS

MODEL	BELT WIDTH (mm)	CONVEYOR LENGTH (m)		MAX CAPACITY (t/h)	CONVEYOR SPEED (m/min)	MOTOR PULLEY (kW)	BELT LENGTH (endless m)	MACHINE WEIGHT (kg)				
		OVERALL LENGTH	APPROX C/C									
BF35-4	350	3.7	3.5	100 (50kg/m)	35/42 or 21/25 (50/60Hz)	1.0 or 1.5	7.5	140				
BF35-5		4.7	4.5				9.5	163				
BF35-6		5.7	5.5				11.5	182				
BF35-7		6.7	6.5				13.5	203				
BF35-8		7.7	7.5				15.5	227				
BF35-9		8.7	8.5				17.5	245				
BF35-10		9.7	9.5				19.5	267				
BF35-11		10.7	10.5				21.5	291				
BF35-12		11.7	11.5				23.5	309				
BF35-13		12.7	12.5				25.5	331				
BF45-4		450	3.7				3.5	100 (50kg/m)	35/42 or 21/25 (50/60Hz)	1.0 or 1.5	7.5	157
BF45-5			4.7				4.5				9.5	184
BF45-6			5.7				5.5				11.5	204
BF45-7	6.7		6.5	13.5	228							
BF45-8	7.7		7.5	15.5	256							
BF45-9	8.7		8.5	17.5	277							
BF45-10	9.7		9.5	19.5	300							
BF45-11	10.7		10.5	21.5	327							
BF45-12	11.7		11.5	23.5	348							
BF45-13	12.7		12.5	25.5	372							
BF60-4	600		3.7	3.5	110 (70kg/m)	35/42 or 21/25 (50/60Hz)	1.5				7.5	189
BF60-5			4.7	4.5							9.5	221
BF60-6			5.7	5.5							11.5	245
BF60-7		6.7	6.5	13.5				272				
BF60-8		7.7	7.5	15.5				304				
BF60-9		8.7	8.5	17.5				329				
BF60-10		9.7	9.5	19.5				356				
BF60-11		10.7	10.5	21.5				388				
BF60-12		11.7	11.5	23.5				412				
BF60-13		12.7	12.5	25.5				489				